#### manual loading vertical-horizontal inclinable packaging machine

Attracts you with its simplicity. Up to 30 packs/min. Activated by a pedal or by double push buttons.

## >> general features

Activated by a pedal or by double push buttons. Vertical inclination from 0 to 80 can be changed thanks to a simple hand wheel. Different inclination change the falling speed of the product enabling the machine to work in both horizontal and vertical position depending of the products. Any products from the fruit and vegetables to the bread, to the sweets, to the seafood/dairy products, cold meats, food or non-food products, like small fittings, small profiles; single products or multiple products.

# >> specific features

The Forming tunnel of the machine is easily adjustable allowing to pack a wide range and sizes of products thanks also to the wide film reel: Up to 680 mm width. Film can be any different kind of polypropylene, polyolefin, perforated bakery film. The packaging is made thanks to a two couples of driven and sealing wheels underneath and a mechanic sealing bar. Same components ISO certificated as our standard packaging machines. All components in contact with the products are in stainless steel.

### >> details




An adjustable tunnel allows the packaging of a lot of different kind of products with wide range of measures.







Sealing wheels and film tensioning .Rotary Stainless steel version is available. pulling and sealing wheels.






Machine can optionally be equipped with an in feed loading pipe for easy products loading.

rier photocell.

PREFERRED PACKAGING ITALY srl - Sede operativa: Via dell'Artigianato, 6 - 36030 San Vito di Leguzzano (Vicenza) Italy Tel. + 39 0445 580093 - Fax + 39 0445 584609 - Tel. e Fax + 39 0445 602907 - info@preferredpack.it - www.preferredpack.it Magazzino e logistica: Via Tolomeo, 11 - 36034 Malo (Vicenza) Italy





Adjustable Bag size. Movements on linear guides.





Inclinable working level from 0° to 90°.

SIEMENS ABB

HIWIN MOTOVARIO

KUHNKE I pizzato



Precise product's detection thanks to bar-

High quality ISO certificated components.

A MITSUBISHI



### >> technical features

ZED

ax 680 mm 00 mm
00 mm
50 mm
) pack per minute
Kw
00 v 3 ph+n+t
250 x1250x1700
70 Kg
) k

Sud flow pack inclinable maching



Inclinable from 0° to 90°.

