automatic tray packer machine

With trays erector for the tray opening and insertion below the multipacks and for the closure around the multipack of the tray cartoon. Carton trays, will be open, formed and placed ready to receive cans (or other products) in multipacks.

>> general features

Tray packer forming machine including an adjustable cardboard magazine moving belt to keep a pile of cartoons in vertical position and move them to a proper pick & place system for the tray positioning to the chain for movement. Box picker arm with pneumatic controls and pneumatic suction pads.

Teethed transportation system, adjustable in width by a touch screen control panel.

Picker unit comprising two pneumatic arms and motorized linear guide controlled by an inverter and Encoder.

>> specific features

Wing closure system with pneumatic control system. Transfer of boxes, position in a "U" shape between the fixed teeth of the chain controlled by an inverter. Box flap folding in motion and not fixed with other systems. Hot melt standard sealing unit. Open trays size min. 150x150 mm - max 500x800 mm. Trays flaps: H30-100 mm. Siemens touch screen control panel. Siemens PLC. Top-quality electric parts. Operation versatility thanks to various programs pre inserted in the PLC. Self-diagnostic feature will alert operator of problem. Easy access electrical control panel with solid state relays and contactors. Emergency stop, CE approved. Installed power: 4kw. Air consumption: Max 200 liters/min. Air pressure: 6Bars. Possibility to run production also as by-pass or even without tray (as optional).

>> details



Opening doors for a complete access.

size and grouping to ensure highest flexibility.



Cartoon magazine for different sizes.

tion.





Hot melt system.

PREFERRED PACKAGING ITALY srl - Sede operativa: Via dell'Artigianato, 34 - 36030 San Vito di Leguzzano (Vicenza) Italy Tel. + 39 0445 580093 - Fax + 39 0445 584609 - Tel. e Fax + 39 0445 602907 - info@preferredpack.it - www.preferredpack.it Magazzino e logistica: Via Tolomeo, 11 - 36034 Malo (Vicenza) Italy





Infeed belt. Adjustable for different products Shacking system before guides insertion.





Adjustable guides for multipack prepara- Completely opening machine.

Electric adjudtment of cartoons magazine.

Final result after tray erection around product.



DRON

arto tray packer machine

>> technical features

Шm

MOD.			
Electric connection		1	400V 50/60Hz 3PH+N+earth. Other voltages are available on request as optional.
Installed power	1		4 kw
Compressed air			6 bar constant
Air consumption	1		Max 200 litres/min.
Colour			RAL 9003
Working height	e .		900 +/- 50mm
Open trays size:		10	Min 150x150mm MAX 500x800mm
Tray flaps	1		30-100mm
Standard capacity			10packs/minute
Special execution			Up to 20packs/minute



Opening doors for an easy and fast access to the area of products passage, for clea-ning and for the cartoons loading.



High precision system for products insertion on cartoons.



Touch screen control panel for an easy and intuitive parameters modification.



Great versatility of use, with cartons of various shapes and sizes. Simple adjustments of the cartons loading system, allow the operator change of size.

Multipacks preparation by the use of movables guides with the possibility to get different multipacks sizes.