

General features

Shrinking tunnels were developed to solve shrinking problems of items of various sizes. They can be used with all shrinking films available on the market. They can be integrated in the packaging machine (so called "combo" version) or just connected to it, ensuring an elegant look and an easy use.

Specific features

Shrinking chamber with hot air total reuse.
Adjustable air-flow and speed.
Digital temperature control.
Automatic turn-off mechanism when temperature drops below 80°C.

Details



Opening chamber available for cleaning and maintenance.




Compact design




Smart & inline design



Opening chamber available for cleaning and maintenance.



Tunnel can be equipped with products compactor to ensure a perfect alignment of products before shrinking.



Motor's fan ventilator is protected and easy extractable.



Flaps for air circulation adjustable from outside.



In this tunnel version (integrated to automatic L sealer) the chamber of the tunnel is movable to have products always running in the middle, while in the new generation EVO tunnel the tunnel is fixed as the centering of the products is done in the EVO side seal machine middle conveyor.

Technical features

Mod.	45T	55T	45T	55TL	75TL
Speed:	24 p/min	24 p/min	35 p/min	35 p/min	25 p/min
Working height:	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm
Tunnel size:	L970 x W1170 x H1570 mm	L970 x W1270 x H1570 mm	L1435 x W1170 x H1570 mm	L1435 x W1170 x H1570 mm	L2610 x W1400 x H1800 mm
Machine's dimensions:	L970 x W450 x H300 mm	L970 x W550 x H300 mm	L1435 x W450 x H300 mm	L1435 x W550 x H300 mm	L1800 x W750 x H400 mm

Mod.	105TL	150TL	200TL	250TL	300TL
Speed:	24 p/min	15 p/min	15 p/min	15 p/min	15 p/min
Working height:	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm	900 +/- 50mm
Tunnel size:	L2600 x W1650 x H1800 mm	L3500 x W2000 x H1850 mm	L3500 x W2500 x H1850 mm	L4000 x W3000 x H1850 mm	L4500 x W3600 x H1850 mm
Machine's dimensions:	L1800 x W1000 x H400 mm	L2500 x W1550 x H400 mm	L2500 x W2000 x H400 mm	L3000 x W2600 x H600 mm	L3500 x W2600 x H600 mm

DM Pack S.r.l.

Plant: Via dell'Artigianato, 34 - 36030 San Vito di Leguzzano (VI) Italy
Contacts: Tel. + 39 0445 580093 - Fax + 39 0445 584609 - Tel. e Fax + 39 0445 602907 -info@dmpack.it - www.dmpack.it



NEOS

Shrink tunnel

EN

NEOS

DM Pack shrink tunnels range is characterized by an attractive line, high functionality, compact and accessible structure.

High quality components, ISO certificated

SIEMENS ABB OMRON HIWIN MOTOVARIO KUHNKE pizzato MITSUBISHI

Electric cabinet on view.
Flaps easy adjustable from outside.
Metallic net easy to clean.

Thanks to the perfect air circulation, it is possible to shrink the film around the product at a low temperature with a great energy saving.

Electric cabinet on view.
Flaps easy adjustable from outside.
Metallic net easy to clean.

Stainless steel versions available.
Big shrink tunnel versions can be equipped with metallic net and a double fan underneath the belt to cool down the product.

Standard height up to 300 mm.

